


FIG. 1



- 1 the body
- 2 coin inserting aperture
- 4 sorting unit
- 5 holding unit
- 6B storing cylinder
- 6C storing cylinder
- 6D storing cylinder
- 6 coin storing unit
- 7 coin repayment unit
- 8 holding cylinder
- 8A holding cylinder
- 8B holding cylinder
- 8C holding cylinder
- 8D holding cylinder
- 9 sorting device
- 10 10 yen coin storing cylinder
- 40 magnetic sensor
- 41 coin passage
- 42 genuineness sorting gate
- 43 first gate
- 44 second gate
- 45 third gate
- 46 fourth gate

007060" 885960

FIG. 2






FIG. 3




12	wiper	18	rotary pulley
16	coin catching plate	18A	projection
16A	hole	19	gear of pulley
16B	slope portion	20	plate
16C	slide groove	20A	straight bevel bar
		20B	rectangle hole
		21	drive gear
		21A	guide bar
		22	first transmission gear
		23	second transmission gear
		24A	pinion gear

3	coins	20	plate
<u>5</u>	holding unit	20A	straight beret gear
8	holding cylinder	25	take-in passage
9	sorting device	26	slope shoot
11	receiving member	26A	concave portion
11A	concave portion	29	damper
<u>12</u>	wiper	29A	rotation shaft
<u>13</u>	coin storing passage	29B	fitting
14	repayment passage	30	solenoid
15	guide shoot	30A	force-giving spring
16	coin catching plate	31	arm
16B	slope portion		
16C	slide groove		
18	rotary pulley		
18A	projection		
19	gear of pulley		

FIG. 5

- | | | | |
|-----|----------------------|-----|---------------------|
| 3 | coins | 20 | plate |
| 8 | holding cylinder | 20A | straight bevel gear |
| 9 | sorting device | 25 | take-in passage |
| 11 | receiving member | 26 | slope shoot |
| 11A | concave portion | 26A | concave portion |
| 12 | wiper | 29 | damper |
| 13 | coin storing passage | 29A | rotation shaft |
| 14 | repayment passage | 29B | fitting |
| 15 | guide shoot | 30 | solenoid |
| 16 | coin catching plate | 30A | force-giving spring |
| 16A | hole | 31 | arm |
| 16B | slope portion | | |
| 16C | slide groove | | |
| 18 | rotary pulley | | |
| 18A | projection | | |
| 19 | gear of pulley | | |


6/12
FIG. 6



- | | | | |
|-----|----------------------|-----|---------------------|
| 3 | coins | 20 | plate |
| 8 | holding cylinder | 20A | straight beret gear |
| 9 | sorting device | 25 | take-in passage |
| 11 | receiving member | 26 | slope shoot |
| 11A | concave portion | 26A | concave portion |
| 12 | wiper | 29 | damper |
| 13 | coin storing passage | 29A | rotation shaft |
| 14 | repayment passage | 29B | fitting |
| 15 | guide shoot | 30 | solenoid |
| 16 | coin catching plate | 30A | force-giving spring |
| 16A | hole | 31 | arm |
| 16B | slope portion | | |
| 16C | slide groove | | |
| 18 | rotary pulley | | |
| 18A | projection | | |
| 19 | gear of pulley | | |

001060" 886E9960

FIG. 7



- | | | | |
|----------|--------------------------|-----------|-----------------------|
| 3 | coins | 56C | slide groove |
| <u>8</u> | holding cylinder | <u>58</u> | drive system |
| 8A | holding cylinder | 58A | rotary pulley |
| 8B | holding cylinder | 58B | guide bar |
| 9B | sort and take-out device | 59 | coin receiving member |
| 56 | coin catching plate | 61A | passage for pole |
| 56A | hole | 62 | supporting plate |
| 56B | concave portion | 63 | solenoid |
| | | 64 | force-giving spring |

096398-090100



- 096398-090100








FIG. 12



- | | |
|-----|---------------------|
| 52 | wiper |
| 56 | coin catching plate |
| 56A | hole |
| 56B | concave portion |
| 57 | moving member |
| 59 | receiving member |
| 59A | coin receiving part |
| 59B | stopping pole |
| 60 | fitting plate |

- | | | | |
|-----------|----------------------------|-----------|-----------------------|
| 3 | coins | 57 | moving member |
| 8A | holding cylinder | 57A | fitting plate |
| 9 | sort and take-out device | <u>58</u> | drive system |
| 51 | receipt-for-storing member | 58A | rotary pulley |
| <u>52</u> | wiper | 58B | guide bar |
| 53 | coin storing passage | 59 | coin receiving member |
| 54 | repayment passage | 59A | coin receiving part |
| 55 | guide shoot | 59B | stopping pole |
| 56 | coin catching plate | 62 | supporting plate |
| 56A | hole | | |
| 56B | concave portion | | |
| 56C | slide groove | | |

FIG. 14



- | | | | |
|-----------|----------------------------|-----|-----------------------|
| 3 | coins | 59 | coin receiving member |
| 8A | holding cylinder | 59A | coin receiving part |
| 9B | sort and take-out device | 59B | stopping pole |
| 51 | receipt-for-storing member | 61 | blocking plate |
| <u>52</u> | wiper | 62 | supporting plate |
| 53 | coin storing passage | | |
| 54 | repayment passage | | |
| 55 | guide shoot | | |
| 56 | coin catching plate | | |
| 56A | hole | | |
| 56B | concave portion | | |
| 56C | slide groove | | |
| 57 | moving member | | |
| <u>58</u> | drive system | | |
| 58A | rotary pulley | | |
| 58B | guide bar | | |